

M700 and M750 Product Information

	M700	M750	M207S	M207R
	■	■		
Temperatures in 8 to 15 Seconds	■	■		
Accurate to within 0.1° F or C	■	■		
Fahrenheit And Celsius Capability	■	■		
Temperature Range F° 34° to 150°	■	■		
Temperature Range C° 0° to 65°	■	■		
Peak Temperature Hold – Displayed on Screen	■	■		
Charging Indicator – Actual Battery Voltage	■	■		
Low Battery Warning on Display	■	■		
Automatic Shut-off After 5 Minutes	■	■		
Automatic Shut-Off Time Determined By Customer	■	■		
Red LED Display With Ambient Light Adjustment	■	■		
Operation Modes Displayed on LED Screen	■	■		
Self Re-Setting Fuse	■	■		
Calibration Check Position	■	■		
Interchangeable With All GLA M207 Probes	■	■		
1253 Memory Locations		■		
RS232 Port Output and Cable		■		
Baud Rate Determined By User		■		
9600 Baud Rate Standard Default		■		
RFID Reader Compatible		■		
Real Time Clock Feature		■		
Information Can Be Downloaded Into Software		■		
Last Four Digits of Tag Displayed On LED		■		
Manual Entry of ID Through Computer Interface		■		
Thermometer Includes M207 Probe and C725 Charger		■		
M750 Thermometer Includes Null Modem Cable		■		
Two Year Warranty O M700 / M750	■	■		
Made In USA By GLA	■	■		
Machined Aluminum Box With Powder Coat Finish	■	■		
Machined Aluminum Inner Protection Rails	■	■		
Size: 3 x 1.75 x 5 inches	■	■		
Size: 7.6 x 4 x 12.7 Centimeters	■	■		
Weight: 22 Ounces	■	■		
Weight 617 Grams	■	■		
M207R Right Angle Probe - 4.0" / 10.0cm			■	
M207R Right Angle Probe - 3.0" / 7.5cm			■	
M207R Right Angle Probe – 1.5" / 7.5cm			■	
M207S Straight Probe – 4.0" / 10.0cm				■
M207S Straight Probe - 3.0" / 7.5cm				■
M207S Straight Probe - 1.5" / 3.75cm				■
C725 Charger (110-230 Volt - compatible for US and International Market)	■	■	■	■
One Year Warranty on Probes	■	■	■	■
Quick use instructions included in English and Spanish or English and French	■	■	■	■
Customer support at: 800.346.1182 / 805.541.3758 / info@gla-ag.com	■	■	■	■